

Product Sheet

Product: **Ascom i62**

- 802.11 a/b/g/n compatibility
- Support for graphical messaging
- Interactive, colour-coded messaging
- Colour display
- Alarm & positioning
- Centralised management



ASCOM i62 - WHEN INTEROPERABILITY AND INTEGRATION REALLY MATTER

Unique .11n performance

As one of the first VoWiFi handsets operating on an 802.11n network, the Ascom i62 is truly unique. It supports deployment of voice over the network without degrading the performance of an existing .11n network capacity.

Superior interoperability

As well as trouble-free WLAN vendor interoperability and scalability, the Ascom Solution has the capacity to integrate and communicate with a comprehensive range of external sources.

Streamlined administration

When it comes to system administration, our web-based Centralized Management system offers many benefits. Over-the-air updates reduce the workload of administrators and centrally stored settings simplify phone replacement and shared handset scenarios. As well as representing continuity and peace of mind for administrators and handset users, this provides increased value.

Product Sheet

i62 Handset Features at a Glance

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> • Colour display • Water, dust and chemical resistant for easy disinfection • Local, central, company phonebook • 18 languages, 1 customisable • Push-button alarm with distinct alarm types | <ul style="list-style-type: none"> • Interactive messaging • Voice mail • Built-in loudspeaker • 3 programmable soft keys • 9 programmable hot keys • Profiles system and personal • Call history list | <ul style="list-style-type: none"> • Vibration alert • Easily replaceable battery for 24/7 use • Centralised management • Support for graphical messaging • Customised sounds • Easy Deployment • Centralised certificate handling |
|--|---|---|

i62 Handset Variant Feature Comparison

	i62 Talker
Centralised management	✓
Central phonebook	✓
Location	✓

i62 Handset Technical Specifications

<p>Dimensions 134x53x26mm</p> <p>Weight (Incl. battery & clip) 135g</p> <p>Display (TFT) 29x35mm</p>	<p>Languages</p> <p>Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese (Brazilian), Russian, Slovakian, Spanish, Swedish, Turkish, + 1 downloadable.</p>	<p>Connectors</p> <p>Multi-purpose connector for battery charging, software download and configuration.</p> <p>Standard 2.5 mm headset connector.</p>
<p>Battery</p> <p>Type: Li-polymer.</p> <p>Speech time: Up to 15 hrs. Stand-by time: Up to 100 hrs. Charge time: 2.5 hrs.</p> <p>Discharge/charge cycles: >=80% capacity left after 400 full charge/discharge cycles.</p>	<p>Telephony</p> <p>Indication: 14 ring signals, flashing LED, vibration.</p> <p>Answer call: Button press or auto answer.</p> <p>Call list storage capacity: 25 received, dialed, missed calls.</p>	<p>Messaging (SMS)</p> <p>Max length: 160 characters from handset, system dependent to handset.</p> <p>Storage: 30 received/sent messages.</p>
<p>Audio</p> <p>Ring signal: Adjustable in 8 steps.</p> <p>Earpiece: Adjustable in 8 steps of 3dB each.</p> <p>Max. sound ring signal level: 88 dBA @ 10 cm.</p> <p>Loudspeaker: Duplex loud speaking function.</p>	<p>Accessoires</p> <p>See accessories sheet.</p>	<p>Environmental</p> <p>Operating temperature: -5°C to +45°C.</p> <p>Storage temperature³: -25°C to +55°C. Enclosure protection: IP44, IEC EN60529. Immunity to electromagnetic fields:</p> <p>10 V/m EN61000-4-3.</p> <p>Immunity to ESD: 8 kV contact discharge, 14 kV air discharge (EN61000-4-2).</p> <p>Free fall test, standard product: IEC 60068-2-32, dropped 12 times from 1 meter.</p> <p>Approved for 12 drops from 1.5 meters.</p>
<p>WLAN</p> <p>Number of subscriptions: 4 systems, automatic or manual selection.</p> <p>VoIP protocol: H.323, H.450, SIP (RFC 3261).</p> <p>Security: 802.11i (TKIP, AES- CCMP), WEP (64/128 bit).</p> <p>Authentication: 802.1x: Original 802.11 open/shared key, WPA-PSK, WPA2- PSK, PEAP-MSCHAPv2, EAP-TLS, EAP-FAST, Authentication certificate.</p> <p>Quality of Service: 802.11e (WMM, U-APSD, TSPEC-based CAC).</p> <p>Network: 802.11a/b/g/n.</p> <p>Roaming: Pre-authentication, PMKSA caching, CCKM, opportunistic key caching.</p>	<p>Licences</p> <p>Add-on licenses: Shared phone, Location (Ekahau) and Man-down/no-movement.</p> <p>Upgrade licenses: i62 Messenger and i62 Protector</p>	
	<p>Certification</p> <p>WiFi Alliance 802.11n including WiFi multimedia</p>	

Dependent of active mode, U-APSD WLAN environment and configuration and handset location relative to system. ²Stand-by time is without activated screensaver. ³Storing Li-Ion batteries at high temperatures can dramatically and permanently reduce capacity. Specifications are subject to change without notice.

pragma

Distributed by:

Pragma
Unit E2, Rock Business Park, The Hollow,
Washington, RH20 3GR
Tel: +44 1903 927100
www.wearepragma.co.uk

Manufactured by: Ascom Wireless Solutions Ascom (Sweden) AB

Grimbodalen 2, SE-417 49 Göteborg, Sweden
www.ascom.com/ws